

**Amendments to the Claims:**

Please cancel claims 2 and 11, and amend claims 1 and 10 as shown in the following listing of claims. This listing of claims will replace all prior versions, and listings, of claims in the application.

1 1. (currently amended) A method of adjusting image-capturing parameters of  
2 an image-capturing device comprising:  
3 capturing a first image and a second image using different settings  
4 of the image-capturing parameters including:  
5 processing raw image data of a captured scene of interest  
6 using a first setting of a selected image-capturing parameter to capture the first  
7 image; and  
8 processing the raw image data using a second setting of the  
9 selected image-capturing parameter to capture the second image;  
10 displaying the first and second images as comparison images for  
11 user selection; and  
12 adjusting current settings of the image-capturing parameters of the  
13 image-capturing device to conform with one of the first and second images  
14 selected by a user.

1 2. (canceled).

1 3. (original) The method of claim 1 wherein the step of capturing the first and  
2 second images includes sequentially capturing a scene of interest using two  
3 different settings of a selected image-capturing parameter to capture the first and  
4 second images.

1 4. (previously presented) The method of claim 3 wherein the selected image-  
2 capturing parameter is selected from a group consisting of exposure period,  
3 aperture and white balance.

1 5. (previously presented) The method of claim 1 wherein the image-capturing  
2 parameters include a parameter selected from a group consisting of exposure  
3 period, aperture, color saturation, contrast, brightness, hue, gamma correction and  
4 white balance.

1 6. (original) The method of claim 1 wherein the step of displaying the first  
2 and second images includes simultaneously displaying the first and second  
3 images.

1 7. (original) The method of claim 1 wherein the step of displaying the first  
2 and second images includes sequentially displaying the first and second images.

1 8. (previously presented) The method of claim 1 further comprising a step of  
2 capturing a third image using the current settings of the image-capturing  
3 parameters as the settings to produce the third image.

1 9. (canceled).

1 10. (currently amended) An imaging system comprising:  
2 an image-capturing device that is configured to electronically  
3 capture images using different settings of image-capturing parameters;  
4 a display device that is configured to visually present a first  
5 captured image and a second captured image, the first captured image  
6 corresponding to first settings of the image-capturing parameters, the second  
7 captured image corresponding to second settings of the image-capturing  
8 parameters; and  
9 a parameter adjuster operatively coupled to the image-capturing  
10 device, the parameter adjuster being configured to adjust current settings of the  
11 image-capturing parameters of the image-capturing device to conform to one of  
12 the first settings and the second settings in response to a user selection between  
13 the first captured image and the second captured image presented on the display  
14 device, the parameter adjuster being configured to direct a processor to process  
15 raw image data of a captured scene of interest using one setting of a selected  
16 image-capturing parameter to capture the first captured image, the parameter  
17 adjuster being further configured to direct the processor to process the raw image  
18 data using another setting of the selected image-capturing parameter to capture the  
19 second captured image.

1 11. (canceled).

1 12. (original) The imaging system of claim 10 wherein the parameter adjuster  
2 is configured to direct the image-capturing device to sequentially capture a scene  
3 of interest using two different settings of a selected image-capturing parameter to  
4 produce the first and second captured images.

1 13. (previously presented) The imaging system of claim 12 wherein the  
2 selected image-capturing parameter is selected from a group consisting of  
3 exposure period, aperture and white balance.

1 14. (original) The imaging system of claim 10 wherein the image-capturing  
2 parameters include a parameter selected from a group consisting of exposure  
3 period, aperture, color saturation, contrast, brightness, hue, gamma correction and  
4 white balance.

1 15. (original) The imaging system of claim 10 wherein the parameter adjuster  
2 is configured to direct the display device to simultaneously display the first and  
3 second captured images.

1 16. (original) The imaging system of claim 10 wherein the parameter adjuster  
2 is configured to direct the display device to sequentially display the first and  
3 second captured images.

1 17. (canceled).

1 18. (original) A method of adjusting image-capturing parameters of an image-  
2 capturing device comprising:  
3 capturing a scene of interest as raw image data using an image  
4 sensor of the image-capturing device;  
5 processing the raw image data using first settings of the image-  
6 capturing parameters to produce a first image of the scene of interest;  
7 processing the raw image data using second settings of the image-  
8 capturing parameters to produce a second image of the scene of interest;  
9 displaying the first and second images for user selection; and  
10 adjusting current settings of the image-capturing parameters of the  
11 image-capturing device to conform with one of the first and second images  
12 selected by a user, the adjusted current settings of the image-capturing parameters  
13 being used by the image-capturing device to capture a subsequent image.

1 19. (previously presented) The method of claim 18 wherein the image-  
2 capturing parameters include at least two parameters selected from a group  
3 consisting of color saturation, contrast, brightness, hue, gamma correction and  
4 white balance.

1 20. (original) The method of claim 18 wherein the step of displaying the first  
2 and second images includes simultaneously displaying the first and second  
3 images.

1 21. (original) The method of claim 18 wherein the step of displaying the first  
2 and second images includes sequentially displaying the first and second images.

1 22. (previously presented) The method of claim 1 wherein the image-capturing  
2 parameters include at least two parameters selected from a group consisting of  
3 exposure period, aperture, color saturation, contrast, hue, gamma correction and  
4 white balance.

1 23. (previously presented) The imaging system of claim 10 wherein the image-  
2 capturing parameters include at least two parameters selected from a group  
3 consisting of exposure period, aperture, color saturation, contrast, hue, gamma  
4 correction and white balance.